

BMS battery management system for lithium rechargeable battery pack

Model: BMS LIBRA10S100LP-BK1

Electrical Characteristics

No.	Test item		Criterion
1	Type of cells	Type	All rechargeable lithium
		Number of cells	5÷10
		Range voltage for single cell	1,5÷4,5 VDC
		Cells in series	yes 5÷10
		Cells in parallels	yes
2	Voltage	Range min/max	7÷45 VDC
		Minimum voltage measured	1 mV
3	Current	Low Current consumption for single cell with auxiliary charger	≤50 µA
		Maximal continuous charging current	8A
		Maximal continuous discharging current	25A or 35A
		Double antiparallel mosfet for charge	yes
		Minimum measured current	10 mA
4	Balance	Type of Balance	Passive
		Number of balance	three type (A,B,C)
		Minimum balance voltage for single cell	1 mV
		Balance current for single cell	100 mA
5	Over charge Protection	Over charge detection voltage	settable ±1mV
		Over charge release voltage	settable ±1mV
6	Over discharge protection	Over discharge detection voltage	settable ±1mV
		Over discharge release voltage	settable ±1mV
7	Over current protection	Over discharge detection current	settable ±1A
		Detection delay time	settable ±1s
8	Temperature	Battery temperature misure	settable ±1°C
		PCB temperature misure	settable ±1°C
9	Time	Real time clock with back-up battery	yes
		auto power off	settable ≥1min
		USB	yes
		PWM opto isolated	no
		TX opto isolated	yes
		Bluetooth	yes
		Led command output	4
		Settable by PC	yes
12	Software of comunication	windows support	yes
13	Comunication with smartphone	Application Android	yes
14	Comunication with smartphone	Application IOS	yes

BMS battery management system for lithium rechargeable battery pack

Model: BMS LIBRA10S100LP-BK1

Memory internal of the BMS

No.	Test item		Criterion
1	Time	Day last charge	yes
		Data of last charge	yes
		Charge cycles	yes
2	Current	Register of Amper/hours	yes
3	Operation data	Internal register	10 parameters
4	Production data	Internal register	4 parameters
5	Historical log data	Register fifo	64 events
6	Historical day register	Register fifo	400 day


BMS battery management system for lithium rechargeable battery pack

Model: BMS LIBRA10S100LP-BK1

Electrical and Mechanical Characteristics

No.	Test item		Criterion
1	Type of core	Micro Controller	16 bit
2	Misure current	Analog-to-Digital Converters	16 bit
3	Misure Voltage	Analog-to-Digital Converters	16 bit
4	Power regulator	Switching Regulators	high efficiency
5	ON/OFF	Switch SPST	yes
6	Efficiency	At maximum power	99,98%
7	Led	State views	discharge/charge
8	Power consumption	Stand By State	≤100 nA
9	Power consumption	ON State, without bluetooth	≤10 mA
10	Power consumption	ON State, with Bluetooth	≤20 mA
11	PCB	Command	FR4
12	Weight	Measure	64 gr.
13	Dimension	Measure	240*50*10mm
14	Temperature	Operating Temperature Range	-20, +70 °C
		Storage Temperature Range	-20, +85 °C

Photo of the product:



Designed by:
www.silidea.it
www.silidea.com